

# DWF

## DIRECT WOOD FLOORING



### Palermo Long - Golden Oak

The Palermo Long Golden Oak laminate flooring faithfully recreates the textures and colours of a natural oak in a more affordable and easier to maintain material. As beautiful as it is hard-wearing, the floor comes with 12mm thick planks and a realistic wood effect design to offer an ideal alternative to a solid wood product. Backed by an AC5 rating and made from premium quality materials, Golden Oak is designed to withstand heavy foot traffic in both modern family homes or in fast-paced commercial spaces. The 1846mm long planks feature 4-sided V-grooves for more authenticity and will suit medium-sized and larger rooms perfectly. To complete your purchase and ensure the perfect feel underfoot, We recommend using a 1-3mm underlay. Using this underlay will provide your amazing new laminate flooring with protection from your subfloor and remove any minor deviations it has, whilst also delivering excellent acoustical performance. Head over to our Underlay page found in our Accessories menu to find the perfect one for you!

#### RANGE DETAILS

Construction	Laminate
Surface	ER / Registered Emboss
Edge Profile	4V Bevel
Thickness (mm)	12
Board Width (mm)	188
Board Length (mm)	1845
Pack Coverage	1.38
Boards per Pack	4
Country of Origin	Germany

#### TECHNICAL DATA

Fire Certification	Cfl-S1
Slip Resistance	DS
Thermal Resistance	0.09 (m <sup>2</sup> K)/W
AC Rating	AC5
Water Rating	<8%
Formaldehyde Rating	E1
VOC Emissions Rating	Low Emissions

#### INSTALLATION GUIDANCE

Fitting System	5G Click
Recommended Underlay	1-3mm Underlay
Expansion Gap	Min. 10mm
Suitable for Underfloor Heating?	Yes - Maximum 27°C
Acclimatisation Time	48 to 72 hours

#### PROPERTIES

Fitting System	5G Click
Recommended Underlay	1-3mm Underlay
Expansion Gap	Min. 10mm
Suitable for Underfloor Heating?	Yes - Maximum 27°C
Acclimatisation Time	48 to 72 hours

#### ROOM SUITABILITY



Living Room



Bedroom



Dining Room



Kitchen



Study



Hallway



Bathroom



Stairs

