

Capri - Travertine Stone

Product Description

Achieve the look of real stone and marble with our collection of Porcelain Tiles, offering luxury style at a fraction of the cost. Available in a variety of contemporary colours and textures, this range exudes sophisticated style with its attention to detail. The matt finish helps provide anti-slip protection ensuring these tiles are safe for your home. Expertly crafted from extremely hardwearing and versatile porcelain, our tiles can be used on floors and walls and benefit from being 100% waterproof.

Our Stone & Marble Tiles are easy to maintain and suitable for underfloor heating, however please note if you have a water heating system then you will need to install an anti-crack mat to prevent your tiles from breaking with the increasing heat.



Range Details	Properties	Technical Data	Technical Specification
Material	Porcelain	Slip Resistance	R9
Finish	Matt	Water Absorption	≤ 0.5%
Thickness	9mm	Breaking Strength	≥1300N
Tile Width	60cm	Resistance to Staining	5
Tile Length	60cm	Frost Resistance	Yes
Pack Coverage	1.44	VOC Emissions Rating	A+
Tiles per Pack	4		
Country of Origin	Spain		
Rectified Edge?	No		

Installation Guidance	Properties
Underlay Required?	No
Expansion Gap	5mm or 10mm With Underfloor Heating
Suitable For Underfloor Heating?	Yes
Installation Suitability	Indoor Floors/Walls

Capri - Travertine Stone

Product Description

Achieve the look of real stone and marble with our collection of Porcelain Tiles, offering luxury style at a fraction of the cost. Available in a variety of contemporary colours and textures, this range exudes sophisticated style with its attention to detail. The matt finish helps provide anti-slip protection ensuring these tiles are safe for your home. Expertly crafted from extremely hardwearing and versatile porcelain, our tiles can be used on floors and walls and benefit from being 100% waterproof.

Our Stone & Marble Tiles are easy to maintain and suitable for underfloor heating, however please note if you have a water heating system then you will need to install an anti-crack mat to prevent your tiles from breaking with the increasing heat.



Range Details	Properties	Technical Data	Technical Specification
Material	Porcelain	Slip Resistance	R9
Finish	Matt	Water Absorption	≤ 0.5%
Thickness	10.5mm	Breaking Strength	≥ 1300 N
Tile Width	80cm	Resistance to Staining	5
Tile Length	80cm	Frost Resistance	Yes
Pack Coverage	1.28	VOC Emissions Rating	A+
Tiles per Pack	2		
Country of Origin	Spain		
Rectified Edge?	Yes		

Installation Guidance	Properties
Underlay Required?	No
Expansion Gap	5mm or 10mm With Underfloor Heating
Suitable For Underfloor Heating?	Yes
Installation Suitability	Indoor Floors/Walls