

EvoCore 360 - Shadow Oak

Product Description

EvoCore 360 offers the key features of Essentials, whilst also showcasing a unique omni-click fitting system which allows for versatility, suitability and style. The fit system allows for unique and eclectic patterns to be created as well as popular herringbone patterns. Tile and wood can be fitted together and colours can even be mixed, extending the possibilities available, and ensuring there is a style and pattern to suit all tastes and preferences.



Range Details	Properties	Technical Data	Technical Specification
Construction	LVT / FOAMED RCB	Fire Certification	BFL - s1.
Species	Oak	Slip Resistance	R10
Wear Layer (mm)	0.55mm	Thermal Resistance	EN ISO 8302.
Edge Profile	DreamClick Micro Bevel	Water Rating	RESISTANT.
Thickness (mm)	5mm	Resistance to Staining	EN ISO 26995
Board Width (mm)	204mm	Wear Rating	EN ISO 24340.
Board Length (mm)	1326mm	Formaldehyde Rating	Class E1
Pack Coverage	2.16m ²	Phthalate Free?	Yes
Boards per Pack	8	VOC Emissions Rating	Low Emissions

Installation Guidance	Properties
Fitting System	DreamClick
Recommended Underlay	EvoCore 360 Underlay
Expansion Gap	8MM
Suitable For Underfloor Heating?	EN ISO 12524.

Room Suitability

