

Herringbone - Golden Oak

Product Description

The warmth and character of solid oak come to life in this LVT flooring. The tiles measure 2.5mm in thickness and come with a durable 0.55mm wear layer. Made to withstand busy environments with ease, the surface is stain, dent, and scuff resistant as well as easy to clean and to maintain. Thanks to the 102mm x 613mm tiles, you can install this floor in various ways, from classic to parquet-style. Complementing feature strips allow you to enhance the design further. We don't recommend laying this product in areas where the temperature will reach 29°C as the product may curl. We also advise that this product be left for 72 hours prior to installation at room temperature.

To complete your purchase and ensure a hard-wearing finish, we recommend using our Impero All-In-One Adhesive.



| Range Details | Properties | Technical Data | Technical Specification |
|-------------------|---------------------|----------------------|----------------------------|
| Construction | Luxury Vinyl Tiles | Fire Certification | Bfl-s1 |
| Species | Oak | Slip Resistance | Class DS |
| Wear Layer (mm) | 0.55mm | Thermal Resistance | 0.067 (m ² K)/W |
| Edge Profile | Micro Bevel | Water Rating | 100% waterproof |
| Thickness (mm) | 2.5mm | Staining Resistance | N/A |
| Board Width (mm) | 102mm | Wear Resistance | class 34 |
| Board Length (mm) | 613mm | Formaldehyde Rating | Class E1 |
| Pack Coverage | 1.25 m ² | VOC Emissions Rating | Low Emissions |
| Boards per Pack | 20 | | |

| Installation Guidance | Properties |
|----------------------------------|----------------------------|
| Fitting System | Stick |
| Recommended Adhesive | Impero All-In-One Adhesive |
| Expansion Gap | 6-8mm |
| Suitable For Underfloor Heating? | Yes |

Room Suitability

