



Tivoli - Dove Oak

Product Description

Are you looking for a flooring solution that combines elegance with resilience? Look no further than our beautiful Tivoli Laminate. Manufactured with 8mm thickness and an impressive AC4 rating, this exceptional flooring option is designed to elevate your space while withstanding the rigours of everyday life.

Available in both modern and neutral colour options, Tivoli Laminate offers realistic wood grain and knot detailing for an authentic appearance. Installation is a breeze thanks to the click fit mechanism, ensuring a snug fit whilst also reducing installation time and costs.



| Range Details | Properties | Technical Data | Technical Specification |
|-------------------|------------|-------------------------------|------------------------------------|
| Construction | Laminate | Fire Certification | Cfl-S1 |
| Surface | Impact | Slip Resistance | DS |
| Edge Profile | 4V Bevel | AC Rating | AC4 |
| Thickness | 8mm | Thermal Resistance | 0.05 (m2K)/W |
| Board Width | 193mm | Water Rating | ≤18% |
| Board Length | 1205mm | Resistance to Staining | Min. 5 (Group 1+2) Min.4 (Group 3) |
| Species | Oak | Wear Resistance | Class 32 |
| Pack Coverage | 1.86m² | Formaldehyde Rating | El |
| Country of Origin | Turkey | VOC Emissions Rating | Low Emissions |

| Installation Guidance | Properties | |
|----------------------------------|--------------------|--|
| Fitting System | Click | |
| Recommended Underlay | 1-3mm Underlay | |
| Expansion Gap | Min 10mm | |
| Suitable For Underfloor Heating? | Yes - Maximum 27°C | |













