

## Bayswater Herringbone - Golden Oak

### Product Description

Golden tones, eye-catching grain, organic lines, and subtle colour variations give this floor a charming rustic appearance. Bayswater Herringbone comes with natural beauty with function. It comes with a tough 2.5mm top layer and a 14mm thickness, offering stability underfoot and durability at the same time. The brushed lacquered finish acts as a protective layer against everyday wear, transforming cleaning into a fuss-free task. Easy to install with the 4G Click system, this engineered wood floor will suit even the busies areas of a family home. The floor is also compatible with underfloor heating, enhancing both the elegance and the comfort of your living spaces. \*When fitting this beautiful Herringbone flooring, it is recommended that you use our Impero Primer with in-built DPM and our Impero Wood Adhesive to ensure your flooring is fitted to perfection



Range Details	Properties	Technical Data	Technical Specification
Finish	Brushed & Lacquered	Fire Certification	Dfl-s1
Species	Oak	Slip Resistance	48
Grade	Character	Thermal Conductivity	0.14 W/mK
Veneer	2.5mm	Wear Resistance	WR1 > (P2000)
Thickness	14mm	PCP Content	not detected
Board Width	110mm	Formaldehyde Rating	E-1
Board Length	660mm	VOC Emissions Rating	340 ug/m3
Pack Coverage	0.5 m <sup>2</sup>		
Boards per Pack	7 boards x 660mm		
Wood Origin	Europe		

Installation Guidance	Properties
Fitting System	Optilock
Recommended Underlay	Timberlay Gold
Expansion Gap	10 mm
Suitable For Underfloor Heating?	Yes
Acclimatisation Time	48 Hours

### Room Suitability

