



## Carpenters Choice Herringbone Vanilla Oak Engineered Wood

## **Product Description**

Mellow tones of vanilla, honey and cream alongside the wonderful knots and unique natural markings give this herringbone floor a truly beautiful appearance that can bring a comfortable feeling into any room. The Carpenter's Choice Herringbone Oak displays wonderful grain variations and organic patterns, and you can rest assured that your new floor will withstand anything a busy home can throw at it, while the lacquered finish will make long-term maintenance easier.



| Range Details   | Properties        | Technical Data       | Technical Specification |
|-----------------|-------------------|----------------------|-------------------------|
| Finish          | Lacquered         | Fire Certification   | Dfl-S1                  |
| Species         | Oak               | Slip Resistance      | NPD                     |
| Grade           | Character         | Breaking Strength    | 37 MPa                  |
| Veneer          | 2.5mm             | Thermal Conductivity | 0.14 W/mK               |
| Thickness       | 14 mm             | Formaldehyde Rating  | E1                      |
| Board Width     | 110mm             | VOC Emissions Rating | A+                      |
| Board Length    | 660mm             |                      |                         |
| Pack Coverage   | 0.5m <sup>2</sup> |                      |                         |
| Boards per Pack | 7                 |                      |                         |
| Wood Origin     | Europe            |                      |                         |

| Installation Guidance            | Properties                 |  |
|----------------------------------|----------------------------|--|
| Fitting System                   | Optilock                   |  |
| Recommended Underlay             | Timberlay Gold             |  |
| Expansion Gap                    | 10mm                       |  |
| Suitable For Underfloor Heating? | Yes - no higher than 29 °C |  |
| Acclimatisation Time             | 48-72 Hours                |  |

## **Room Suitability**













