

Classic Natural Oak - Brushed & Oiled

Product Description

Our Classic Natural Oak brings the wonderful natural wood floor look effortlessly to your home, with its beautiful light brown tones add that relaxed charm to your home, Classic Natural Oak has plenty of character with a lacquered 3mm solid top layer which features gorgeous swirl marks, natural wood knots and other beautiful natural flourishes, this flooring is designed to offer great stability and durability even in the busiest areas.



Range Details	Properties	Technical Data	Technical Specification
Finish	Brushed & Oiled	Fire Certification	Dfl-S1
Species	Oak	Slip Resistance	0.4-0.6
Grade	Rustic	Thermal Conductivity	
Veneer	3mm	Wear Resistance	5000rEN 660-
Thickness	14mm	PCP Content	PCP < 5 x 10 ⁻⁶ n
Board Width	150mm	Formaldehyde Rating	â‰‰0,008 mg/m ³
Board Length	300 - 1200mm	VOC Emissions Rating	â‰‰5 ppm
Pack Coverage	1.44m ²		
Boards per Pack	8pcs		
Wood Origin	Europe		

Installation Guidance	Properties
Fitting System	Tongue & Groove
Recommended Underlay	Timberlay Silver
Expansion Gap	10 mm
Suitable For Underfloor Heating?	Yes
Acclimatisation Time	48-72 Hours

Room Suitability

