



## Manhattan Golden Smoked Oak

## **Product Description**

Are you looking for a change? Our highly popular Manhattan Golden Smoked Oak is a showstopper, with delicious milk chocolate and caramel tones. Its darker brown accents are enchanting to the eye and will add beauty to any home. Manhattan Golden Smoked Oak is an engineered wood floor with character and elegance, a wonderful combination that makes it a versatile decor choice, suitable for all types of homes and interiors. Brushed to give the wood grain and knots the best chance to shine through, in all their glory and smoked to bring out an elegant aged appearance. It is finished with a lacquer for added protection and provides a beautiful finish.



| Range Details   | Properties          | Technical Data       | Technical Specification    |
|-----------------|---------------------|----------------------|----------------------------|
| Finish          | Brushed & Lacquered | Fire Certification   | Dfl-S1                     |
| Species         | Oak                 | Slip Resistance      | NPD                        |
| Grade           | Rustic              | Thermal Conductivity | 0,16W/mK                   |
| Veneer          | 3mm                 | Wear Resistance      | USRV22                     |
| Thickness       | 14mm                | PCP Content          | Not Detected               |
| Board Width     | 190mm               | Formaldehyde Rating  | E1 (0,2mg/m3)              |
| Board Length    | 1900mm              | VOC Emissions Rating | Test Method: YC/T 207-2014 |
| Pack Coverage   | 2.888m²             |                      |                            |
| Boards per Pack | 8                   |                      |                            |
| Wood Origin     | France              |                      |                            |

| Installation Guidance            | Properties        |  |
|----------------------------------|-------------------|--|
| Fitting System                   | Tongue and Groove |  |
| Recommended Underlay             | Timberlay Gold    |  |
| Expansion Gap                    | 10 mm             |  |
| Suitable For Underfloor Heating? | Yes               |  |
| Acclimatisation Time             | 48 Hours          |  |

## **Room Suitability**













