

DIRECT WOOD FLOORING

## Oxford Herringbone Vintage Oak

## **Product Description**

Are you looking for a change? Subtle smoky undertones mixed with dark chocolate shades, mesmerizing grains and knots as well as eye-catching tones make this engineered floor a perfect choice for any interior. Our Oxford Herringbone Vintage Oak adds character and natural charm to classic or modern living spaces. Designed to stand the test of time, the floor measures 14mm in thickness and comes with a tough 3mm top layer. The surface boasts a brushed finish that enhances the features of solid oak.



Range Details	Properties	Technical Data	Technical Specification
Finish	Brushed & Lacquered	Fire Certification	Dfl-S1
Species	Oak	Slip Resistance	
Grade	Rustic	Thermal Conductivity	0,16W/mK
Veneer	3mm	Wear Resistance	USRV22
Thickness	14mm	PCP Content	Not Detected
Board Width	90mm	Formaldehyde Rating	E1 (0,2mg/m3)
Board Length	450mm	VOC Emissions Rating	Test Method: YC/T 207-2014
Pack Coverage	1.94 4m <sup>2</sup>		
Boards per Pack	48		
Wood Origin	France		

Installation Guidance	Properties	
Fitting System	Tongue and Groove	
Recommended Underlay	Timberlay Gold	
Expansion Gap	10mm	
Suitable For Underfloor Heating?	Yes	
Acclimatisation Time	48 Hours	

## **Room Suitability**



