

Bayswater Herringbone - Unfinished Oak

Product Description

An unfinished Bayswater Herringbone oak, gives you the canvas to create a floor that matches your home perfectly through a selection of oils available in our accessory section. Versatile and practical, the floor can either complement classic interiors or provide a refreshing contrast to minimalist homes. *When fitting this beautiful Herringbone flooring, it is recommended that you use our Impero Primer with in-built DPM and our Impero Wood Adhesive to ensure your flooring is fitted to perfection



Range Details	Properties	Technical Data	Technical Specification
Finish	Unfinished	Fire Certification	Dfl-s1
Species	Oak	Slip Resistance	48
Grade	Character	Thermal Conductivity	0.14 W/mK
Veneer	2.5mm	Wear Resistance	WR1 > (P2000)
Thickness	14mm	PCP Content	not detected
Board Width	110mm	Formaldehyde Rating	E-1
Board Length	660mm	VOC Emissions Rating	340 ug/m3
Pack Coverage	0.5 m ²		
Boards per Pack	7 pcs. x 660mm		
Wood Origin	Europe		

Installation Guidance	Properties
Fitting System	Optilock
Recommended Underlay	Timberlay Gold
Expansion Gap	10 mm
Suitable For Underfloor Heating?	Yes
Acclimatisation Time	48 Hours

Room Suitability

