

Bayswater Herringbone - Natural Oak

Product Description

With a sublime natural tone, a captivating profile and stunning features that need to be seen closely to grasp their beauty, Bayswater Herringbone - Natural Oak is a paragon of engineered wood flooring completed at the highest standards of quality. Brushed Lacquered to capture and lift every organic shape from the depths of the 2.5mm natural oak wear layer, Bayswater Herringbone - Natural Oak is a fantastic addition to any home *When fitting this beautiful Herringbone flooring, it is recommended that you use our Impero Primer with in-built DPM and our Impero Wood Adhesive to ensure your flooring is fitted to perfection



Range Details	Properties	Technical Data	Technical Specification
Finish	Brushed & Lacquered	Fire Certification	Dfl-s1
Species	Oak	Slip Resistance	48
Grade	Character	Thermal Conductivity	0.14 W/mK
Veneer	2.5mm	Wear Resistance	WR1 > (P2000)
Thickness	14mm	PCP Content	not detected
Board Width	110mm	Formaldehyde Rating	E-1
Board Length	660mm	VOC Emissions Rating	340 ug/m3
Pack Coverage	0.5 m ²		
Boards per Pack	7 boards x 660mm		
Wood Origin	Europe		

Installation Guidance	Properties
Fitting System	Optilock
Recommended Underlay	Timberlay Gold
Expansion Gap	10 mm
Suitable For Underfloor Heating?	Yes
Acclimatisation Time	48 Hours

Room Suitability

