

## Bayswater Herringbone - Urban Oak

### Product Description

Bayswater Herringbone Urban Oak comes with plenty of appeal with an undeniable contemporary charm. This engineered herringbone floor can look spectacular in any setting, from classic country homes with antique furnishings to urban flats with eclectic interiors or a modern, open plan home. Several coats of high quality lacquer help shield the oak from staining while also providing extra strength and durability, for a floor that will keep its stunning features intact for years to come.



Range Details	Properties	Technical Data	Technical Specification
Finish	Brushed & Lacquered	Fire Certification	Dfl-s1
Species	Oak	Slip Resistance	48
Grade	Character	Thermal Conductivity	0.14 W/mK
Veneer	2.5mm	Wear Resistance	WR1 > (P3000)
Thickness	14mm	PCP Content	not detected
Board Width	110mm	Formaldehyde Rating	E-1
Board Length	660mm	VOC Emissions Rating	340 ug/m3
Pack Coverage	0.5 m <sup>2</sup>		
Boards per Pack	7 pcs. x 660mm		
Wood Origin	Europe		

Installation Guidance	Properties
Fitting System	Optilock
Recommended Underlay	Timberlay Gold
Expansion Gap	10 mm
Suitable For Underfloor Heating?	Yes
Acclimatisation Time	48 Hours

### Room Suitability

