

## Studio Natural Oak Brushed & Oiled

### Product Description

Are you looking to invest in flooring that will stand the test of time? Then look at our Studio Natural Oak, which will introduce a touch of natural grace and rustic charm to any room in your home. This feature rich wood is not only extremely durable with its 3mm solid wood top layer, it has a stable and reliable plywood base too. Gorgeous light brown tones and lighter cream hues are complimented with striking darker grains. This flooring really showcases the authentic wood knots and adds natural charm to any space. Studio Natural Oak will look stunning situated in the kitchen or dining room. The undeniable rustic appeal of this engineered wood floor, and natural oil finish ensures that your flooring can deal with all aspects of a busy home. The Studio range gives you the look of a genuine solid wood floor, at an affordable price.



| Range Details   | Properties         | Technical Data       | Technical Specification    |
|-----------------|--------------------|----------------------|----------------------------|
| Finish          | Brushed & Oiled    | Fire Certification   | Dfl-S1                     |
| Species         | Oak                | Slip Resistance      | NPD                        |
| Grade           | Rustic             | Thermal Conductivity | 0,16W/mK                   |
| Veneer          | 3mm                | Wear Resistance      | USRV22                     |
| Thickness       | 14mm               | PCP Content          | Not Detected               |
| Board Width     | 125mm              | Formaldehyde Rating  | E1 (0,2mg/m3)              |
| Board Length    | 300 - 1200mm       | VOC Emissions Rating | Test Method: YC/T 207-2014 |
| Pack Coverage   | 1.8 m <sup>2</sup> |                      |                            |
| Boards per Pack | 12                 |                      |                            |
| Wood Origin     | France             |                      |                            |

| Installation Guidance            | Properties        |
|----------------------------------|-------------------|
| Fitting System                   | Tongue and Groove |
| Recommended Underlay             | Timberlay Gold    |
| Expansion Gap                    | 10mm              |
| Suitable For Underfloor Heating? | Yes               |
| Acclimatisation Time             | 48 Hours          |

### Room Suitability

