

Studio Honey Oak Lacquered

Product Description

Are you sick and tired of replacing your flooring constantly? Studio Honey Oak has a richly warm colour palette with bronze and copper tones, with delicate rust hues in a stunning display of organic shades and natural beauty. The 10mm plywood core is extremely durable and strong, while the 2mm wear layer of oak is perfectly suited for a busy property. The top 2mm layer has been gently lacquered to bring out its best features and offer you an amazing canvas for your current decor, while the overall 12mm thickness ensures extra durability for your floor.



Range Details	Properties	Technical Data	Technical Specification
Finish	Lacquered	Fire Certification	Dfl-S1
Species	Oak	Slip Resistance	NPD
Grade	Rustic	Thermal Conductivity	0,16W/mK
Veneer	3mm	Wear Resistance	USRV22
Thickness	14mm	PCP Content	Not Detected
Board Width	125mm	Formaldehyde Rating	E1 (0,2mg/m3)
Board Length	300 - 1200mm	VOC Emissions Rating	Test Method: YC/T 207-2014
Pack Coverage	1.8 m ²		
Boards per Pack	12		
Wood Origin	France		

Installation Guidance	Properties
Fitting System	Tongue and Groove
Recommended Underlay	Timberlay Gold
Expansion Gap	10mm
Suitable For Underfloor Heating?	Yes
Acclimatisation Time	48 Hours

Room Suitability

