

## Loft Golden Smoked Oak Brushed & Lacquered

### Product Description

Are you looking for a change? The dark and rich golden hues of Loft Golden Smoked Oak engineered wood flooring offer a fascinating look for any room, from classically decorated to minimalist and modern or a creative and eclectic decor. Its captivating intensity is matched only by its superior lacquered finish that accentuates the alluring tones of the natural wood. Planks vary in length for a more authentic and rustic tone, and make Loft Golden Smoked Oak easy to lay in a smaller room or in an open plan area in equal measure. Versatile, gorgeous, extremely durable giving any home that sophisticated look.



| Range Details   | Properties          | Technical Data       | Technical Specification    |
|-----------------|---------------------|----------------------|----------------------------|
| Finish          | Brushed & Lacquered | Fire Certification   | Dfl-S1                     |
| Species         | Oak                 | Slip Resistance      | NPD                        |
| Grade           | Rustic              | Thermal Conductivity | 0,16W/mK                   |
| Veneer          | 3mm                 | Wear Resistance      | USRV22                     |
| Thickness       | 14mm                | PCP Content          | Not Detected               |
| Board Width     | 150mm               | Formaldehyde Rating  | E1 (0,2mg/m3)              |
| Board Length    | 300 - 1200mm        | VOC Emissions Rating | Test Method: YC/T 207-2014 |
| Pack Coverage   | 1.44 m <sup>2</sup> |                      |                            |
| Boards per Pack | 8                   |                      |                            |
| Wood Origin     | France              |                      |                            |

| Installation Guidance            | Properties        |
|----------------------------------|-------------------|
| Fitting System                   | Tongue and Groove |
| Recommended Underlay             | Timberlay Gold    |
| Expansion Gap                    | 10 mm             |
| Suitable For Underfloor Heating? | Yes               |
| Acclimatisation Time             | 48 Hours          |

### Room Suitability

